



AMT U80W1.1

Tweeter

Samples available: Immediately
Start of sale: Immediately

AMT U60W1.1 and **AMT U80W1.1** could be described as the small and the large all-rounder of this product range. Both can be used in small or medium 2-way and 3-way systems. **AMT U80W1.1** offers additional dynamic range. Both convince with the decisive quality features of the **AMT U.Series** with **Mundorf diaphragm**: Exceptionally low K3 / K5 distortion data, a truly powerful music performance within the entire application range and, at the same time, the fine micro-dynamics and richness of music details that distinguish all **Mundorf AMT's**.




Specifications

Nominal Impedance	4 Ω
DC Resistance (R_{dc}) (Z_{min})	4.4 Ω
Sensitivity (2,83 V / 1m) ¹	94 dB
Resonance Frequency (FS)	2150 Hz
Frequency Response (-6dB)	1.8 kHz - 31 kHz
Frequency Response (-10dB) ¹	1.4 kHz - 34 kHz
Crossover from (filter 12dB/6dB/Oct.)	2.0 kHz / 3.0 kHz
Nominal Frequency Range ³	2.2 kHz - 31 kHz
Power Handling, long term ^{1,2}	15 W
Power Handling, short term ^{1,2}	90 W
Max. Input Voltage, long term ^{1,2}	7.7 V _{rms}
Max. Input Voltage, short term ^{1,2}	19 V _{rms}
Effective Piston Area	31.4 cm ²
Total Weight	0.360 kg
Face Plate	optional


1) according to IEC 60268-5
 2) via High Pass Filter, Butterworth 2200 Hz 12 dB/Okt.
 3) according to power measurement

Interactive 3D Model




Measurements

SPL Horizontal 0° - 15° - 30° - 45°




SPL Vertical 0° - 10° - 20° - 30°




Measurements


SPL - Impedance




Harmonic Distortion 2.83 V




Waterfall




SPL - Phase




Impulse Response




Step Response



Dimensions



	Dimensions	Tolerance
Length	95 mm	+ 0,5 mm
Width	55 mm	+ 0,5 mm
Depth including terminal	45 mm	+/- 1 mm



All measurements are in mm.