

NERO-12MWN400D

AUDIENCE

12" - Midwoofer - 400W - 98dB

- Proprietary cone paper material with manila pulp
- Strong neodymium motor
- 3" voice coil with APC (Advanced Polymer Coating)
- Interleaved Sandwich Voice coil technology
- Cast aluminium chassis
- Minimum damping fiber glass voice coil former
- Copper sleeve for low inductance and reduced distortion



Dimensions & Weight

| | |
|-----------------------------|---|
| Overall Diameter | 322.5 mm (12.6 in) |
| Bolt Circle Diameter | 306.5 mm (12.06 in) |
| Baffle Cutout Diameter | 287 mm (11.29 in) |
| Mounting Depth | 133.3 mm (5.24 in) |
| Flange and Gasket Thickness | 11.9 mm (0.47 in) |
| Net Weight | 4.15 Kg (9.15 lb) |
| Shipping Box | 354 x 354 x 182 mm (13.93 x 13.93 x 7.16 in) |
| Gross Weight | 5.24 Kg (11.55 lb) |

Specs :

| | |
|---------------------------------|--------------------------------------|
| Nominal Impedance | 8 Ohm |
| Minimum Impedance | 5.3 Ohm |
| AES Power Handling (1) | 400 W |
| Maximum Power Handling (2) | 800 W |
| Sensitivity (1W/1m) | 98 dB |
| Frequency Range | 66 - 6100 Hz |
| Voice Coil Diameter | 75.6 mm (3 in), Interleaved sandwich |
| Winding Material | Copper |
| Former Material | Till |
| Winding Depth | 17.6 mm |
| Magnetic Gap Depth | 10 mm (0.39 in) |
| Flux Density | 1.07 T |
| Magnet | Neodymium |
| Basket Material | Aluminium die cast |
| Demodulation | Extendend copper cap |
| Cone Surround | Triple roll with damping glue |
| NET Air Volume filled by driver | 2.15 liters |
| Spider Profile | Single constant height waves |
| Weather Resistant | Yes |

Thiele Small Parameters

| | |
|-------------|-----------------------|
| Fs | 66 Hz |
| Re | 5.4 Ohm |
| Qes | 0.55 |
| Qms | 8.98 |
| Qts | 0.52 |
| Vas | 31.1 liters |
| Sd | 543.3 cm ² |
| Xmax (3) | 7.13 mm |
| Xdamage (4) | 16 mm |
| Mms | 78.8 g |
| BI | 17.8 Tm |
| Le | 0.19 mH |
| Cms | 0.07 mm/N |
| Rms | 3.63 Kg/s |
| Eta Zero | 1.55 % |
| EBP | 120 |

Recone Kit

1P000OPSB012

NOTES :

- (1) AES standard, test mode with continuous pink noise signal (6 dB crest factor; 2 hours) within the Fo to 10Fo power calculated on rated nominal impedance. Loudspeaker in free air
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Xmax= ((Winding depth - magnetic gap depth)/2) +(magnetic gap depth/3)
- (4) Maximum excursion (p-p) before permanent damage
- (5) T/S parameters measured on drive units that are broken in using Klippel LPM Measurement System.

