



## DT-28N

Order No.: 10.4020

Price upon request

### PRODUCTINFOS

#### Neodymium hi-fi tweeter, 50 W, 8 $\Omega$

- Outstanding sound characteristics
- Very linear reproduction even of lower frequencies
- High efficiency
- 28 mm extra efficient silk cone
- Perfectly small front plate for high-performance speaker systems of the smallest size possible
- Mounting into perfect D'Appolito arrangements also in lying centres due to low magnetic dispersion

### TECHNICAL SPECIFICATIONS

#### DT-28N

Impedance (Z)	8 $\Omega$
Frequency range	fx-20,000 Hz
Resonant frequency (fs)	1,200 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,000 Hz

**DT-28N**

Power rating (RMS)	50 W
Peak music power output (MAX)	100 W
Sensitivity	94 dB/W/m
Voice coil diameter	Ø 28 mm
Magnet diameter	Ø 46 mm
Mounting cutout	Ø 50 mm
Mounting depth	16.7 mm
Dimensions	55 x 55 x 20 mm
Width	55 mm
Height	55 mm
Depth	20 mm
Admiss. ambient temp.	0-40 °C
Weight	0.074 kg
Packing unit	1