



MRH-300

Order No.: 11.2010

Price upon request

PRODUCTINFOS

PA mid-high range horn

- Horn made of very robust glass fibre reinforced ABS plastic
- 35.6 mm (1.4") flange connection with standard 4-hole screw connection (Ø 101.6 mm)
- Consistent radiation pattern due to constant directivity design
- Can be mounted turned by 90°
- Recommended minimum crossover frequency: 1 kHz

Klang+Ton 01/2016

"The MenhirL is an extra transparent speaker. It provides a dynamic and pleasant sound for most versatile applications. We can experience a very emotional sound with this speaker which meets every requirement - that's how a speaker should be."

Reader's project MenhirL in the Klang+Ton using SP-38A/500BS, MRD-300 and AKB-400DSP

Klang+Ton 03/2013

"Great 1.4" horn/driver combination (MRD-300 with MRH-300) with excellent measured values for PA and hi-

fi applications with sufficient power reserves. Both components feature a very neat workmanship.”

TECHNICAL SPECIFICATIONS

MRH-300

Frequency range	1,000-20,000 Hz
Mounting cutout	281 x 281 mm
Mounting depth	110 mm
Radiation angle (vert./hor.)	40°/90°
Dimensions	315 x 315 x 120 mm
Weight	1.31 kg