



SPH-174KE

6½ 100W

Order No.: 10.5950

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speaker, 50 W, 8 Ω

- Hi-fi bass-midrange speaker of classic design
- High-quality Kevlar cone
- Robust sheet steel basket with 4-hole screw connection
- Very linear frequency response
- For universal use in closed, bass-reflex and TML cabinets
- Including plastic trim ring for basket (Ø 175 mm x 11 mm)

Klang+Ton, 5/2018

"Bass-midrange speaker with excellent technical features available at an attractive price and particularly suitable for closed cabinets."

HOBBY HiFi 06/2018

"An excellent bass-midrange speaker for a cost-efficient 2-way project. Hobby HiFi concept MONA, edition 06/2018"



TECHNICAL SPECIFICATIONS

SPH-174KE

Equivalent volume (Vas)

8Ω Impedance (Z)

f3-8.000 Hz Frequency range

Resonant frequency (fs) 42 Hz Power rating (RMS) 50 W 100 W Peak music power output (MAX)

Sensitivity 88 dB/W/m

Suspension compl. (Cms) 0.98 mm/N

Moving mass (Mms) 14.23 g

Mech. Q factor (Qms) 2.59

Electr. Q factor (Qes) 0.64

Total Q factor (Qts) 0.51

DC resistance (Re) $6.39~\Omega$

26 I

Ø 145 mm

Force factor (BxL) 5.91 Tm

Voice coil induct. (Le) 0.43 mH

Voice coil diameter Ø 25 mm

Voice coil former aluminium

Linear excursion (X_{MAX}) ± 3 mm

Eff. cone area (Sd) 137 cm²

Magnet weight 320 g

Magnet diameter Ø 80 mm

Mounting cutout Mounting depth 68 mm

Mounting hole diameter Ø 158 mm

Hole spacing X-axis 111.7 mm

Hole spacing Y-axis 111.7 mm

Dimensions Ø 168 mm x 75 mm

Outside diameter Ø 168 mm

Width Ø 168 mm

Depth 75 mm

Admiss. ambient temp. 0-40 °C

Weight 0.78 kg

Packing unit 1

6.5" Type of speaker



SPH-174KE - Page: 3

