



| PARAMETERS | |
|-----------------------------|-----------------|
| Impedance | 4 ohms |
| Re | 4.3 ohms |
| Le | 0.10 mH @ 1 kHz |
| Fs | 224 Hz |
| Qms | N/A |
| Qes | N/A |
| Qts | 0.78 |
| Mms | 1.61 g |
| Cms | 0.0003 mm/N |
| Sd | N/A |
| Vd | N/A |
| BL | 3.63 Tm |
| Vas | N/A |
| Xmax | N/A |
| VC Diameter | 25 mm |
| SPL | N/A |
| RMS Power Handling | 24 watts |
| Usable Frequency Range (Hz) | N/A |

- ### FEATURES
- Small size; just under 2" diameter, about 7/8" high
 - Pre-applied 3M™ VHB™ adhesive for quick, durable installation
 - Rare-earth neodymium motor and a proprietary voice coil
 - 4 ohms impedance for use with small, Class D amplifiers
 - 24 watt RMS power handling for high output

- ### APPLICATIONS
- Invisible home theater and multi-room audio
 - Electronic gaming machines
 - Advertising signage
 - Point-of-purchase displays
 - Multimedia exhibits
 - Commercial distributed audio
 - Kiosks
 - Automotive audio
 - Bathroom tubs and showers

